



INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Acoustical Screws • Eye Lag Sharp Point • Zinc

Size	TPI	Ctn Qty	Daggerz™ Part Number	Hole Diameter	Thread Length	Point
14 x 3	10	1,000	ELSZ1430	3/16"	1-5/8"	Sharp

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Zinc Finish provides 24 hour minimum salt spray corrosion resistance
<i>application:</i>	used to attach wire for interior suspended ceiling systems; drywall or insulation to wood

Meets or exceeds the following specifications:

ICC-ES®
ESR-5423



ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1002	Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs
AC 233	Acceptance Criteria for dowel-type fasteners used in wood

Ultimate Value Chart

DIAMETER	1/2" Plywood	5/8" Plywood	3/4" Plywood	2 x 4
#14	434	475	626	1030

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

Scan QR Code to view ICC report, including additional testing results.

ELSZ.1124